CYPrefab

Product datasheet - EN

Weifang Chuangyue Integrated Housing Co., Ltd.
Weifang, Shandong, China
sales@cyprefab.com | WhatsApp +86 183 6563 6536 | www.cyprefab.com

Knock-Down Modular Building - 6000 x 3000 x 2820 mm

KD-6000 | Ships as loose components - the densest packing in the range, 12 to 17 units per 40HQ

Specifications

Length	6,000 mm (236.2 in)
Width	3,000 mm (118.1 in)
Height	2,820 mm (111 in)
Floor area	18 m² (193.8 ft²)
Units per 40HQ container	12-17
MOQ	2 sets
Lead time	20 days per 200 sets
Packed / folded height	Knock-down - loose components
Unit weight	On request
Installation	2 people - 1 unit/day
Fire rating (by core material, B1 to A)	B1-A
Frame thickness options	2.0 / 2.2 / 2.5 / 2.75 / 3.0 / 3.5 mm
Core material options	Rock wool / Glass wool / PU / PIR

Standard scope

- Galvanized steel frame kit - top beams, bottom beams, corner posts
- Wall and roof sandwich panels
- Floor substrate and floor covering
- Steel door and PVC window
- Electrical kit - distribution box, switches, sockets, LED light, industrial plug
- Fastener, sealant and rainwater downpipe set

The approved quotation and drawings govern the final configuration. Unknown project-specific values remain on request.